








OBJECT POSITION DETECTOR WITH EDGE MOTION FEATURE

Patent number: WO9607966
Publication date: 1996-03-14
Inventor: ALLEN TIMOTHY P (US); FAGGIN FEDERICO (US); GILLESPIE DAVID (US); MILLER ROBERT J (US)
Applicant: SYNAPTICS INC (US); ALLEN TIMOTHY P (US); FAGGIN FEDERICO (US); GILLESPIE DAVID (US); MILLER ROBERT J (US)
Classification:
 - **International:** G06F3/033; G06K11/16
 - **European:** G06F3/033Z4S2, G06F3/033D2, G06F3/023A4
Application number: WO1995US11177 19950901
Priority number(s): US19940300630 19940902

Also published as:

 EP0777875 (A1)
 EP0777875 (B1)

Cited documents:

 EP0574213
 US5374787
 EP0609021
 JP6139022
 JP62126429
 more >>

Abstract of WO9607966

A proximity sensor system includes a sensor matrix array having a characteristic capacitance on horizontal and vertical conductors connected to sensor pads. The capacitance changes as a function of the proximity of an object or objects to the sensor matrix. The change in capacitance of each node in both the X and Y directions of the matrix due to the approach of an object is converted to a set of voltages in the X and Y directions. These voltages are processed by circuitry to develop electrical signals representative of the centroid of the profile of the object, i.e., its position in the X and Y dimensions. Noise reduction and background level setting techniques inherently available in the architecture are employed. The speed of the cursor movement depends on the one of the display it resides.

